Autobrade Red
Air Tools For The Body Shop

AUTOMOTIVE

Parts Page Reorder No. APD00•15
Effective December, 2000

Die Grinder
3,200 RPM

Model:
18200

Air Motor and Machine Parts

⚠WARNING **Always operate, inspect and maintain this tool in accordance with the Safety Code for portable air tools (ANSI B186.1) and any other applicable safety codes and regulations. Please refer to Dynabrade's Warning/Safety Operating Instructions for more complete safety information.**



Index Key

No.	Part #	Description
1	**18434**	Collet Cap
2	**18433**	Collet Insert – 1/4"
3	**18437**	Spindle
4	**18905**	Cap
5	**18906**	Felt
6	**18741**	Bearing (2)
7	**18907**	Gear Carrier
8	**18743**	Pin (2)
9	**18738**	Needle Bearing (2)
10	**18737**	Pinion Gear (2)
11	**18736**	Annular Gear
12	**18740**	Housing Lock Ring
13	**18438**	Rubber Gasket
14	**18428**	Bearing
15	**18436**	Pin
16	**18427**	Front End Plate
17	**18739**	Rotor
18	**18426**	Rotor Blade (4/pkg.)
19	**18424**	Cylinder
20	**18423**	Cylinder Pin
21	**18422**	Rear End Plate
22	**18421**	Bearing
23	**18420**	Valve Screw
24	**18419**	O-Ring
25	**18418**	O-Ring
26	**18417**	Regulator
27	**18416**	Valve Spring
28	**18415**	O-Ring
29	**18413**	Valve Stem
30	**18414**	O-Ring
31	**18400**	Motor Housing
32	**18412**	Valve Bushing
33	**18401**	Silencer
34	**18402**	Washer
35	**18403**	O-Ring
36	**18404**	Deflector
37	**18405**	Air Inlet
38	**18411**	Stop Rod
39	**18410**	Safety Lever Spring
40	**18408**	Throttle Lever
41	**18407**	Lever Pin
42	**18409**	Spring Pin
43	**18435**	Wrench (2)

KEY

- **O** Oil: **O_1 = Air Lube**
- **G** Grease: **G_1 = Lubriplate 630AA**
- **A** Adhesive: **A_2 = Loctite #271**
- **T** Torque: **N•m x 8.85 = In. - lbs.**

See reverse side for Important Operating, Maintenance and Safety Instructions.

Autobrade Red Important Operating, Maintenance and Safety Instructions

Carefully read all instructions before operating or servicing any Dynabrade® Abrasive Power Tool.
Warning: Hand, wrist and arm injury may result from repetitive work motion and overexposure to vibration.
Important: All Dynabrade air tools must be used with a Filter-Regulator-Lubricator to maintain all warranties.

Operating Instructions:

Warning: Eye, face, respiratory, sound and body protection must be worn while operating power tools. Failure to do so may result in serious injury or death. Follow safety procedures posted in workplace.

1. With power source disconnected from tool, securely fasten abrasive/accessory on tool.
2. Install air fitting into inlet bushing of tool. **Important:** Secure inlet bushing of tool with a wrench before attempting to install the air fitting to avoid damaging valve body housing.
3. Connect power source to tool. Be careful not to depress throttle lever in the process.
4. Check tool speed with tachometer. If tool is operating at a higher speed than the RPM marked on the tool or operating improperly, the tool should be serviced to correct the cause before use.

Maintenance Instructions:

1. Check tool speed regularly with a tachometer. If tool is operating at a higher speed than the RPM marked on the tool, the tool should be serviced to correct the cause before use.
2. Some silencers on air tools may clog with use. Clean and replace as required.
3. All Dynabrade rotary vane style air motors should be lubricated. Dynabrade recommends one drop of air lube per minute for each 10 SCFM (example: if the tool specifications state 40 SCFM, set the drip rate of your filter-lubricator at 4 drops per minute).
   Dynabrade Air Lube (P/N **95842**: 1pt. 473ml.) is recommended.
4. All Dynabrade geared tools should be greased. Dynabrade recommends greasing this tool every 50 hours of use.
5. It is strongly recommended that all Dynabrade rotary vane air tools be used with a Filter-Regulator-Lubricator to minimize the possibility of misuse due to unclean air, wet air or insufficient lubrication. Dynabrade recommends the following: **11405** Air Line Filter-Regulator-Lubricator — Provides accurate air pressure regulation, two-stage filtration of water contaminants and micro-mist lubrication of pneumatic components.
   Operates 40 SCFM @ 100 PSI has 3/8" NPT female ports.
6. Use only genuine Dynabrade replacement parts. To reorder replacement parts, specify the **Model #**, **Serial #**, and **RPM** of your machine.
7. Mineral spirits are recommended when cleaning the tool and parts. Do not clean tool or parts with any solvents or oils containing acids, esters, keytones, chlorinated hydrocarbons or nitro carbons.

Safety Instructions:

Products offered by Dynabrade should not be converted or otherwise altered from original design without expressed written consent from Dynabrade, Inc.



- **Important:** User of tool is responsible for following accepted safety codes such as those published by the American National Standards Institute (ANSI).
- Operate machine for one minute before application to workpiece to determine if machine is working properly and safely before work begins.
- Always disconnect power supply before changing abrasive/accessory or making machine adjustments.
- Inspect abrasives/accessories for damage or defects prior to installation on tools.
- Please refer to Dynabrade's Warning/Safety Operating Instructions Tag (Reorder No. **95903**) for more complete safety information.
- **Warning:** Hand, wrist and arm injury may result from repetitive work, motion and overexposure to vibration.

Autobrade Red Tool Warranty

Following the reasonable assumption that any inherent defect which might prevail in a product will become apparent to the user within **6 months** from the date of purchase, "Autobrade Red" tools are warranted against defects in workmanship and materials under normal use and service.
We shall, at our option, repair or replace at our factory, any "Autobrade Red" tool which shall, within 6 months after delivery to the original purchaser, indicate upon our examination to have been defective.

Our obligation is contingent upon proper use of "Autobrade Red" tools in accordance with factory recommendations, instructions and practices.
The warranty shall not apply in these cases:

1. Normally wearable parts such as bearings, rotor blades, etc.
2. Consumables such as sanding pads, etc.
3. Misuse, neglect in maintaining tool or tool modification.
4. Lack of lubrication or evidence of rust, dirt or corrosion.
5. Tools requiring normal tune-up or cleaning.
6. Tools being used after they are badly worn such as using ratchet with worn yoke.
7. Ratchets, anvils damaged by excessive hand torquing.
8. Use in production-type applications.

Products to be considered for warranty must be sent back to our factory, transportation prepaid by the user. Please send tool back to attention of "Repair Department" with note fully explaining the nature of the problem along with a copy of original invoice indicating model and serial number.

Return product to:
Dynabrade, Inc.
Attn: Repair Department
8989 Sheridan Dr.
Clarence, NY 14031

Visit Our Web Site: www.dynabrade.com

Autobrade Red
Air Tools For The Body Shop

DYNABRADE®

DYNABRADE Automotive Aftermarket 8989 Sheridan Drive • Clarence, NY 14031-1490 • Phone: (716) 631-0100 • Fax: 716-631-2073
©DYNABRADE, INC., 2000
PRINTED IN USA